

POLYPROPYLENE CONTAINERS
CONTENITORI POLIPROPILENE



REANO

Made of expanded polypropylene (PPE), suitable for protecting food from thermal stress thanks to the insulating properties of the expanded polymer which guarantees a thermal drop compliant with the UNI EN 12571:1999 standard. Polypropylene is expanded with CO₂, without CFCs and HCFCs, and has no residual blowing agents. It has a closed cell structure which gives it excellent characteristics of energy dissipation in impacts and specific thermal resistance. Expanded Polypropylene is mainly composed of air (in relation to density it can reach 98% of air) and only 2% of pure hydrocarbon structural material, it is 100% recyclable and in infinite cycles without releasing residues into the environment or losing its chemical-physical characteristics.

Realizzati in polipropilene espanso (PPE), idonei a proteggere gli alimenti da sollecitazioni termiche grazie alle proprietà coibentanti del polimero espanso che garantisce una caduta termica conforme alla norma UNI EN 12571:1999. Il polipropilene è espanso con CO₂, senza CFC e HCFC, e non ha agenti di espansione residui. Ha una struttura a celle chiuse che gli conferisce eccellenti caratteristiche di dissipazioni di energia negli urti e di resistenza termica specifica. Il Polipropilene Espanso è composto prevalentemente da aria (in relazione alla densità può raggiungere il 98% di aria) e solo dal 2% di materiale strutturale di puro idrocarburo, è riciclabile al 100% e a cicli infiniti senza rilascio di residui nell'ambiente o perdita di caratteristiche chimico-fisiche.



NEW

Insulated GN container SMARTHEATER

Contentitore isothermico
Thermobehälter
Conteneur isotherme
Contenedor isotérmico

art.	cm. ext.	int.	GN	lt.
44983-01	40,6x60,5x37,6	34x54x26,7	1/1	49

Power outlet on the back of the container. Operating temperature -40 +120°C. 220-240V. 50 Hz. 100W. (Resistance) 65°C. Capacity: 2 x GN 1/1 100 mm. or submultiples. – Presa corrente su retro contenitore. Temperatura di esercizio -40 +120°C. 220-240V. 50 Hz. 100W. (Resistenza) 65°C. Capacità: 2 x GN 1/1 100 mm. o sottomultipli.





NEW

Insulated GN container SMARTHEATER

Contentitore isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor isotérmico

art.	cm. ext.	int.	GN	lt.
44983-02	50x65x61	33x54x48	1/1	83

Power outlet on the back of the container. Operating temperature -40 +120°C. 220-240V. 50 Hz. 165W. (Resistance) 65°C. Capacity: 2 x GN 1/1 200 mm. or submultiples. – Presa corrente su retro contenitore. Temperatura di esercizio -40 +120°C. 220-240V. 50 Hz. 165W. (Resistenza) 65°C. Capacità: 2 x GN 1/1 200 mm. o sottomultipli.



NEW

Insulated container SMARTHEATER

Contentitore isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor isotérmico

art.	cm. ext.	int.	lt.
44983-03	60x72x63	40x60x50	128

Power outlet on the back of the container. Operating temperature -40 +120°C. 220-240V. 50 Hz. 165W. (Resistance) 65°C. Capacity: 9 trays 60x40 mm. Presa corrente su retro contenitore. Temperatura di esercizio -40 +120°C. 220-240V. 50 Hz. 165W. (Resistenza) 65°C. Capacità: 9 vassoi 60x40 mm.



Insulated container UNIVERSAL PN

Contentitore isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor isotérmico

art.	cm.	h.	lt.
44986-17	61x43	25,0	33,8
44986-21	61x43	29,5	42,8
44986-28	61x43	36,5	56,7

Dim. int cm. 54,5x36,5x17 /x21,5 /x28,5.



Insulated container GN 1/2

Contentitore isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor isotérmico

art.	cm.	h.	lt.
44972-20	41,5x32	28,5	20,3
44972-25	41,5x32	32,0	21,6
44972-33	41,5x32	40,0	31,2

Dim. int cm. 35x27x21,5 /x25 /x33.



Insulated container GN 1/1

Contentitore isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor isotérmico

art.	cm.	h.	lt.
44970-10	60x40	17	20,2
44970-15	60x40	23	31,2

Dim. int cm. 54x34x11 /x17.

REANO





Insulated container GN 1/1

Contentitore isothermico

Thermobehälter

Conteneur isotherme

Contenedor isotérmico

art.	cm.	h.	lt.
44970-20	60x40	27	38,6
44970-34	60x40	34	52,3

Dim. int cm. 54x340x21 /x28.



Insulated container PLUS GN 1/1

Contentitore isothermico

Thermobehälter

Conteneur isotherme

Contenedor isotérmico

art.	cm.	h.	lt.
44978-20	68x44,5	30	45,6

Dim. int cm. 56x37x22.



Insulated pastry container

Contentitore isothermico pasticceria

Konditorei-Thermobehälter

Conteneur isotherme à pâtisserie

Contenedor isotérmico para pastelería

art.	cm.	h.	lt.
44974-21	68,5x48,5	27	55,8
44974-27	68,5x48,5	33	71,7
44974-31	68,5x48,5	37	82,3

Dim. int cm. 62,5x42,5x21 /x26 /x31.



Insulated container HANDTOP

Contentitore isothermico

Thermobehälter

Conteneur isotherme

Contenedor isotérmico

art.	cm.	h.	lt.
44961-06	71,5x40	31,5	45

Dim. int cm. 55x34x24. Incorporated ergonomic handles. For GN 1/1. – Maniglie ergonomiche incorporate. Trasporta GN 1/1.



Insulated container TROLLEYBOX

Contentitore isothermico

Thermobehälter

Conteneur isotherme

Contenedor isotérmico

art.	cm.	h.	lt.
44961-04	42x42	60	60

Dim. int cm. 36x36x46.



Insulated container BOXSHOP

Contentitore isothermico

Thermobehälter

Conteneur isotherme

Contenedor isotérmico

art.	cm.	h.	lt.
44961-02	41,5x32	32	21,6

Dim. int cm. 35x27x25



Insulated container PIZZABOX

Contentitore isothermico

Thermobehälter

Conteneur isotherme

Contenedor isotérmico

art.	cm.	h.	lt.
44961-03	42x42	34,5	36

Dim. int cm. 36x36x28. With steam release system. – Con sistema di rilascio del vapore.



Insulated container PORTER GN 1/1

Contentitore isothermico

Thermobehälter

Conteneur isotherme

Contenedor isotérmico

art.	cm.	h.	lt.
44987-11	65x50	61	83

Dim. int cm. 54x33x48. For GN 1/1. 12 slides. Per GN 1/1. 12 guide.



Insulated container PORTER MAXI

Contentitore isothermico

Thermobehälter

Conteneur isotherme

Contenedor isotérmico

art.	cm.	h.	lt.
44987-60	72x60	63	128

Dim. int cm. 60x40x50. For pastry trays 60x40. 9 slides. – Per teglie 60x40. 9 guide.



Insulated container GN CRYSTAL

Contentitore isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor isotérmico

art.	cm.	h.	lt.
44968-00	60x40	30	45,4

Dim. int cm. 54x34x24. Inside crystallized and therefore perfectly smooth, rigid and waterproof.
 Interno cristallizzato perfettamente liscio, rigido e impermeabile.



Dolly, aluminum/ABS

Carrello, alluminio/ABS
 Fahrgestell, Aluminium/ABS
 Chariot, aluminium/ABS
 Carro, aluminio/ABS

art.	cm.	for/per
44975C50	58,5x58,5	44975-50
44987C11	68x52	44987-11
44987C60	75x61	44987-60
44987C62	62x42	44968&44970



Eutectic pad

Accumulatore di freddo
 Kühlakku
 Cartouche eutectique
 Placa eutética

art.	cm.	GN
44979-04	32,5x26,5x3	1/2
44979-05	53x32,5x3	1/1
44979-06	60x40x3	-

Temp. 0/-21°C.



Heat accumulator

Accumulatore di caldo
 Wärmespeicher
 Accumulateur de chaleur
 Acumulador de calor

art.	cm.	GN
44979-02	53x32,5x3	1/1

Temp. 0/+65°C.



Insulated box

Box isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor individual isotérmico

art.	cm.	h.
44976-04	44x38	12

3 sections for dishes ø 12 h 6 cm or 16x16 cm.
 3 vani per piatti ø 12 h 6 cm o 16x16 cm.



Insulated box DOMUS

Box isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor individual isotérmico

art.	cm.	h.
44976-02	42,5x26,5	16,5

2 sections for dishes 18x18 cm.
 2 vani per piatti 18x18 cm.



Insulated box MONOKING

Box isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor individual isotérmico

art.	cm.	h.
44976-01	48,5x35	16

2 insulated sections for dishes size 18x18 cm.
 2 vani coibentati per piatti 18x18 cm.



Insulated box THERMOKING

Box isothermico
 Thermobehälter
 Conteneur isotherme
 Contenedor individual isotérmico

art.	cm.	h.
44976-03	47x37	18,5

Release latch lid. Usefull height 11,5 cm.
 Coperchio a incastro. Altezza utile 11,5 cm.



Food container

Pietanziera
 Speisenbehälter
 Porte-manger
 Contenedor comida

art.	Ø cm.	h. cm.
44977-12	12	6

SS

REANO



MODULAR SYSTEM BASE=LID EXTENSIBLE HEIGHT SISTEMA MODULARE BASE=COPERCHIO ALTEZZA ESTENSIBILE



Modular system, the base and lid are the same element and due to the extender insert it is possible to increase capacity. Equipped with rotation system that allows steam to escape.

Sistema modulare, base e coperchio sono lo stesso elemento e grazie all'inserto estensore è possibile aumentare la capacità. Provvisto di sistema rotabile, per la fuoriuscita del vapore.



Base and lid

Base e coperchio
Basis und Abdeckung
Base et couvercle
Base y tapa

art.	cm. ext.	int.
44975-50	57x57x9,5	51x51x6,3



Extender

Estensore
Aufsatz
Réhausse
Extensión

art.	cm. ext.	int.
44975H50	57x57x9,5	51x51x7,5x9,5



PADERNO



NEW
PE

Insulated container GN 1/1

Contentitore isothermico GN 1/1
Thermobehälter GN 1/1
Conteneur isotherme GN 1/1
Contenedor isotérmico GN 1/1

art.	cm. ext.	int.	Kg.
44937-01	68x46x74	53x35x50	21

LLDPE and polyurethane. Keeps food hot or cold up to 6+ hours. Stackable. – LLDPE e poliuretano. Mantiene il cibo caldo o freddo fino a 6 ore. Impilabile.



NEW
PE

Dolly

Carrello
Fahrgestell
Chariot
Carro

art.	cm.	Kg.
44937-02	68x48x25	6,58

LLDPE. Omnidirectional casters.
LLDPE. Ruote omnidirezionali.

